

Keysight Technologies

M9341A PXIe Digital I/O

M9341B PXIe Digital/Analog I/O

Data Sheet



Unlocking Measurement Insights

For more information:

Contact your NSCA & Tra-Cal Small Business Partner:

Email info@nscainc.com or call your local sales rep today at 301-527-9200.



M9341A

Overview

The Keysight M9341A Digital I/O with the 24-bit digital I/O connector and triggering ports provides communication signals between the PXI vector network analyzer (VNA) installed in the same PXI chassis and an external handler.

This allows the PXI VNA such as the Keysight M937xA and M9485A to be used in an automated test environment, where devices to be tested are inserted into a test fixture by a part handler, and sorted into pass/fail bins by the handler after testing is complete. By connecting the part handler to the M9341A digital I/O connector, the VNA and part handler can synchronize their activities in a way that makes automated testing possible.

The M9341A digital I/O also compatible with the 24-bit digital I/O connector on the rear panel of the Keysight PNA and ENA Series.

Key specifications/features

- Digital I/O for communication for the PXI VNA with external peripherals (i.e. handler)
- Synchronized measurements with the PXI VNA in an automated test environment
- Compatible with the 24-bit digital I/O connector on the PNA and ENA



M9341B

Overview

The Keysight M9341B PXIe Digital and Analog I/O is equipped with a 24-bit digital I/O and an 8-bit digital I/O to allow users to control the device under test (DUT) directly with serial or parallel digital signals¹. For example, the signals from the M9341B can be applied to select operation modes of the RF front-end module which integrates power amplifiers, switches, low noise amplifiers, duplexer or filters in a single component. The operation with the M9341B is synchronized with the measurement sweep by the Keysight PXI VNA such as the M937xA Series or the M9485A, greatly improving measurement throughput.

For more comprehensive analysis, the M9341B has four analog input connectors to allow sensing of DC voltages from the DUT. The measured DC voltage can be displayed on the PXI VNA screen. The 1-slot module also supports two variable DC source outputs to control the DUT, while the DC source current can be monitored during measurements.

Key specifications/features

- 8-bit digital I/O for controlling DUT operation mode with serial/parallel signals
- 24-bit digital I/O for communication for the PXI VNA with external peripherals (i.e. handler)
- Synchronized DC measurements with the PXI VNA. Two DC source outputs (up to ± 10 V) with current monitor functions and four DC source inputs for sensing DC voltages from the DUT



1. Serial signals from 8-bit I/O can provide up to 4-channels RFFE-like interface with software selectable clock rate (25 MHz maximum). Please refer to the help file for detail.

Specifications

Definitions

Specification (spec.):

Warranted performance. All specifications apply at 25 °C (± 5 °C) range ambient and module temperature between 27 °C to 39 °C as reported by the module, unless otherwise stated, and 45 minutes after the module has been turned on.¹ Specifications include guard bands to account for the expected statistical performance distribution, measurement uncertainties, and changes in performance due to environmental conditions.

Typical (typ.):

Expected performance of an average unit which does not include guardbands. It is not covered by the product warranty.

General Characteristics:

A general, descriptive term that does not imply a level of performance.

Boundary Conditions:

If the same boundary conditions fall under more than one category in a table, apply the best value.

1. Not only chassis power on but also VNA firmware execution is required to turn on the module.

24 Bit Digital I/O Specification

Description	General Characteristics	Typical
Connector Type	CHAMP 0.8mm, 36 pos Receptacle ¹	
Input Signal		
Logic	3.3 V TTL	
Input Voltage Range	-0.5 V to + 5.5 V	
High-level Input Voltage	+2.0 V Min	
Low-level Input Voltage	+0.8 V Max	
Output Signal		
Logic	3.3 V TTL	
High-level Output Current	-5 mA	
Low-level Output Current	+3 mA	
Output Impedance		100 Ω
Power Supply		
Output Voltage		+4.5 V min, +5.5 V max
Maximum Output Current		100 mA

8 Bit Digital I/O Specification (M9341B Only)

Description	General Characteristics	Typical
Connector Type	ST series, 10 pos receptacle	
Power Supply (VIO)²		
Output Voltage		+3.3 V, +1.8 V, or +1.2 V
Voltage Accuracy		$\pm 5\%$
Maximum Output Current		100 mA
Input Signal		
Input Voltage Range		0 V to VIO
Minimum High-level Input Voltage		+2.0 V (at VIO = +3.3 V) +1.17 V (at VIO = +1.8 V) +0.78 V (at VIO = +1.2 V)
Maximum Low-level Input Voltage		+0.8 V (at VIO = +3.3 V) +0.63 V (at VIO = +1.8 V) +0.42 V (at VIO = +1.2 V)
Output Signal		
Minimum High-level Output Voltage		VIO - 0.1 V (at I _o = -100 μ A)
Maximum Low-level Output Voltage		+0.1 V (at I _o = 100 μ A)

1. M9341A-001 provides conversion cable to the 36-pin centronics, female which is compatible with ENA and PNA handler I/F.
2. Some wait time may be required until the voltage reaches the setting value at voltage setting change. See help for more detail.

Analog I/O Specification (M9341B Only)

Description	Specification	Typical/ General Characteristics
Input Ports		
Number of Ports		4
Connector Type		MCX female
Input Voltage Range	$\pm 10\text{ V}$, $\pm 5\text{ V}$, and $\pm 1\text{ V}$ (selectable)	
Input Impedance		10 M Ω (nom), > 1 k Ω (at power off state)
Measurement Accuracy ¹	At measurement time = 10 ms $\pm(0.1\% \text{ reading} + 0.2\% \text{ range})$	
Damage Level		$\pm 15\text{ V}$
Output Ports		
Number of Ports		2
Connector Type		MCX female
Output Voltage Range	$\pm 10\text{ V}$	
Output Voltage Resolution		1 mV
Maximum Output Current	Mode 1: $\pm 500\text{ mA}$ (Port 1) and $\pm 100\text{ mA}$ (Port 2) Mode 2: $\pm 50\text{ mA}$ (Ports 1 and 2)	
Output Impedance (at Port)		Mode 1: 0 Ω (nom), Mode 2: 50 Ω (nom)
Output Voltage Ripple and Noise		2 mVrms (20 Hz – 20 MHz)
Output Voltage Accuracy ^{1,2}	$\pm(0.2\% + 20\text{ mV})$ at no load with user compensation	$\pm(0.14\% + 14\text{ mV})$ at no load with user compensation $\pm(0.42\% + 40\text{ mV})$ at no load without user compensation
Output Current Monitor Accuracy		At measurement time = 10 ms Mode 1: $\pm(1\% + 7\text{ mA})$ Mode 2: $\pm(1\% + 1\text{ mA})$

Sync Ports Specification

Description	Connector Type	Typical
Sync 1 to 3	SMB male	
Logic		3.3 V TTL



Miscellaneous

Description	General Characteristics
Size	1 PXIe slot, compatible with PXI hybrid slots
Dimensions	212 mm x 20 mm x 128 mm
Weight (net)	330 g (M9341A), 490 g (M9341B)
Power Drawn from Chassis³	5.2 W max (M9341A), 32.0 W max (M9341B) +3.3 V: 0.73 A (M9341A), 2.80 A (M9341B) +5 V: 0 A +12 V: 0.23 A (M9341A), 1.96 A (M9341B) -12 V: 0 A

1. This specification is applied at single usage in the chassis and may be affected by grounding condition.
2. Validation of user compensation: 1 hour and $\pm 3\text{ }^{\circ}\text{C}$ from user compensation. Additional error (typ): 6 mV at 100 mA output (load $\geq 12.1\text{ }\Omega$); 21 mV at 500 mA output (load $\geq 2.2\text{ }\Omega$)
3. At maximum load: Output current from Analog Out Port 1, Analog Out Port 2, +5VIO of 24-bit I/O, and VIO of 8-bit I/O are 500 mA, 100 mA, 100mA, and 100 mA, respectively.


General Characteristics


EMC, safety, environment and compliance

Description	Specification
<p>EMC</p> 	<p>European Council Directive 2014/30/EC IEC 61326-1:2012 EN 61326-1:2013 CISPR 11:2009 +A1:2010 EN 55011: 2009 +A1:2010 Group 1, Class A IEC 61000-4-2:2008 EN 61000-4-2:2009 4 kV CD / 8 kV AD IEC 61000-4-3:2006 +A1:2007 +A2:2010 EN 61000-4-3:2006 +A1:2008 +A2:2010 3 V/m, 80-1000 MHz, 1.4 - 2.0 GHz / 1V/m, 2.0 - 2.7 GHz, 80% AM IEC 61000-4-4:2004 +A1:2010 EN 61000-4-4:2004 +A1:2010 2 kV power lines / 0.5 kV signal lines IEC 61000-4-5:2005 EN 61000-4-5:2006 1 kV line-line / 2 kV line-ground IEC 61000-4-6:2008 EN 61000-4-6:2009 3 V, 0.15-80 MHz, 80% AM IEC 61000-4-8:2009 EN 61000-4-8:2010 30A/m, 50/60Hz IEC 61000-4-11:2004 EN 61000-4-11:2004 0.5-300 cycle, 0% / 70%</p>
<p>ICES/NMB-001</p>	<p>ICES-001:2006 Group 1, Class A</p>
	<p>AS/NZS CISPR11:2004 Group 1, Class A</p>

General Characteristics continued

EMC, safety, environment and compliance

Description	Specification
	<p>KN11, KN61000-6-1 and KN61000-6-2 Group 1, Class A</p> <p>South Korean Class A EMC declaration: Information to the user: This equipment has been conformity assessed for use in business environments. In a residential environment this equipment may cause radio interference.</p> <p>※ This EMC statement applies to the equipment only for use in business environment.</p> <div style="border: 1px solid black; padding: 10px; margin: 10px 0;"> <p style="text-align: center;">사용자 안내문</p> <p style="text-align: center; color: blue;">이 기기는 업무용 환경에서 사용할 목적으로 적합성평가를 받은 기기로서 가정용 환경에서 사용하는 경우 전파간섭의 우려가 있습니다.</p> </div> <p>※ 사용자 안내문은 “업무용 방송통신기자재”에만 적용한다.</p>

Environment	
	<p>This product complies with the WEEE Directive (2002/96/EC) marking requirements. The affixed label indicates that you must not discard this electrical/electronic product in domestic household waste.</p> <p>Product Category: With reference to the equipment types in the WEEE Directive Annex I, this product is classed as a “Monitoring and Control instrumentation” product.</p> <p>Do not dispose in domestic household waste.</p> <p>To return unwanted products, contact your local Keysight office</p>


General Characteristics continued

Analyzer environmental specifications


Operating environment	General characteristics
Temperature	0 to 55 °C ambient 0 to 55 °C module temperature
Humidity	20% to 80% at wet bulb temperature < +29 °C (non-condensation)
Altitude	0 to 2,000 m (0 to 6561 feet)
Vibration	0.21 G maximum, 5 Hz to 500 Hz
Non-operating environment	General characteristics
Temperature	-40 °C to +70 °C
Humidity	20% to 90% at wet bulb temperature < +40 °C (non-condensation)
Altitude	0 to 4,572 m (0 to 15,000 feet)
Vibration	0.5 G maximum, 5 Hz to 500 Hz

Dimensions

M9341A




M9341B



Evolving

Our unique combination of hardware, software, support, and people can help you reach your next breakthrough. **We are unlocking the future of technology.**



From Hewlett-Packard to Agilent to Keysight

myKeysight

myKeysight

www.keysight.com/find/mykeysight

A personalized view into the information most relevant to you.

KEYSIGHT SERVICES

*Accelerate Technology Adoption.
Lower costs.*

Keysight Services

www.keysight.com/find/service

Our deep offering in design, test, and measurement services deploys an industry-leading array of people, processes, and tools. The result? We help you implement new technologies and engineer improved processes that lower costs.



Three-Year Warranty

www.keysight.com/find/ThreeYearWarranty

Keysight's committed to superior product quality and lower total cost of ownership. Keysight is the only test and measurement company with three-year warranty standard on all instruments, worldwide. And, we provide a one-year warranty on many accessories, calibration devices, systems and custom products.



Keysight Assurance Plans

www.keysight.com/find/AssurancePlans

Up to ten years of protection and no budgetary surprises to ensure your instruments are operating to specification, so you can rely on accurate measurements.

Keysight Channel Partners

www.keysight.com/find/channelpartners

Get the best of both worlds: Keysight's measurement expertise and product breadth, combined with channel partner convenience.

www.keysight.com/products/m9341a

www.keysight.com/products/m9341b

For more information on Keysight Technologies' products, applications or services, please contact your local Keysight office. The complete list is available at: www.keysight.com/find/contactus

Americas

Canada	(877) 894 4414
Brazil	55 11 3351 7010
Mexico	001 800 254 2440
United States	(800) 829 4444

Asia Pacific

Australia	1 800 629 485
China	800 810 0189
Hong Kong	800 938 693
India	1 800 11 2626
Japan	0120 (421) 345
Korea	080 769 0800
Malaysia	1 800 888 848
Singapore	1 800 375 8100
Taiwan	0800 047 866
Other AP Countries	(65) 6375 8100

Europe & Middle East

Austria	0800 001122
Belgium	0800 58580
Finland	0800 523252
France	0805 980333
Germany	0800 6270999
Ireland	1800 832700
Israel	1 809 343051
Italy	800 599100
Luxembourg	+32 800 58580
Netherlands	0800 0233200
Russia	8800 5009286
Spain	800 000154
Sweden	0200 882255
Switzerland	0800 805353
	Opt. 1 (DE)
	Opt. 2 (FR)
	Opt. 3 (IT)
United Kingdom	0800 0260637

For other unlisted countries:

www.keysight.com/find/contactus
(BP-2-23-17)



www.keysight.com/go/quality

Keysight Technologies, Inc.
DEKRA Certified ISO 9001:2015
Quality Management System

This information is subject to change without notice.
© Keysight Technologies, 2016, 2017
Published in USA, May 15, 2017
5992-1856EN
www.keysight.com